



產品規格

Name	Variable Area Type Flow Meter
Fluid Type	WATER
Connection Size	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"
Connection Type	JIS 10K / ANSI 150LB / PT / NPT / OTHER
Body Material	SS304 / SS316 / CS
Float Material	SS304 / SS316
Tube Material	GLASS / PC
Seal Material	NEOPRENE
Alarm Switch	NONE / HI / LO / HI & LO
Max. Temperature	60-100°C Based on the chosen type
Max. Pressure	6-20kg/cm ² Based on the chosen type
Accuracy	±3%FS

尺寸表(mm)

Thread	25	32	40	50	65	80	100			
L (mm)	100	100	120	120	120	120	160			
Flange	25	32	40	50	65	80	100	125	150	200
L (mm)	50	50	50	50	50	50	50	50	50	50

流量範圍

Tube Size	Normal Flow Range	
	WATER (L/MIN)	最小刻度 (L/MIN)
25	35-180	5
32	70-360	10
40	110-550	20
50	220-1100	50
65	450-2200	100
80	700-3300	100
100	900-4500	100
125	1200-6000	200
150	2000-10000	200
200	3000-13000	200

選型範例

F06 - 02 - S - 50 - J - G - S - N - 50 - N

Body Material

S: SS304 W: SS316 I: CS

Tube Size

25: DN25 32: DN32 40: DN40
 50: DN50 65: DN65 80: DN80
 100: DN100 125: DN125
 150: DN150 200: DN200

Connection Type

J: JIS 10K A: ANSI 150LB P: PT
 N: NPT O: OTHER

Tube Material

G: GLASS P: PC

Float Material

S: SS304 W: SS316

Seal Material

N: NEOPRENE

Connection Size

25: 1" 32: 1-1/4" 40: 1-1/2" 50: 2" 65: 2-1/2"
 80: 3" 100: 4" 125: 5" 150: 6"

Alarm Switch

N: NONE H: HI L: LO A: HI & LO