



## 產品規格

品名	視流器		
視窗	標準長式	標準短式	小球
安裝型式	JIS 10K / ANSI 150LB / DIN PN16 / PT / NPT / 衛生夾接		
安裝尺寸	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2"
本體材質	SS304 / SS316 / SS316L / PVC / PP / PVDF / CPVC		
視窗材質	GLASS / PC / ACRYLIC / OTHER		
墊片材質	NEOPRENE / VITON / TEFLON / OTHER		
最大耐溫	80°C		
最大耐壓	4-6kg/cm <sup>2</sup>		

## 標準長式尺寸(mm)

F	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"	8"
H	100	100	100	100	120	120	120	150	150	150	140	140
L	210	240	240	240	260	260	260	300	300	310	310	310

## 標準短式尺寸(mm)

F	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
H	90	90	90	110	110	110	110	140	140	140	140
L	114	118	118	142	142	142	146	176	176	180	184

## 小球尺寸(mm)

F	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"
H	70	70	100	100	240	240
L	105	105	140	140	300	310

## 選型範例

F08 - 02 - L - J - 50 - S - G - N

### 視窗

L: 標準長式 S: 標準短式 B: 小球

### 安裝型式

J: JIS 10K A: ANSI 150LB D: DIN PN16  
P: PT N: NPT G: 衛生夾接

### 安裝尺寸

15: 1/2" 20: 3/4" 25: 1" 32: 1-1/4"  
40: 1-1/2" 50: 2" 65: 2-1/2" 80: 3"  
100: 4" 125: 5" 150: 6" 200: 8"

### 本體材質

S: SS304 W: SS316 X: SS316L V: PVC  
P: PP D: PVDF C: CPVC

### 視窗材質

G: GLASS P: PC A: ACRYLIC  
X: OTHER

### 墊片材質

N: NEOPRENE V: VITON  
T: TEFLON X: OTHER